

SUBJECT: 2025 INTERNATIONAL SNOWPLOW PURCHASE

DATE: APRIL 15, 2025

PRESENTED BY: KURT KOWAR, P.E., PUBLIC WORKS DIRECTOR

SUMMARY:

Staff recommends approval for the purchase of one (1) 2026 International HV515 tandem-axle snowplow chassis from McCandless Truck Center, LLC (Sourcewell contract #032824-NVS) and the upfitting of that chassis with a plow, spreader, and wing system through Holman (CDOT competitive bid award # 371002039) for a total purchase price of \$420,121.29.

The snowplow will be equipped with:

- A 12' front plow and a 9' wing plow (Henderson equipment.)
- 15' stainless steel dump body with electric tarp system.
- Henderson 14' FSH-II salt/sand spreader with integrated Force America hydraulic control system.
- Features including LED lighting, backup camera system and wing guidance laser for improved safety.

This vehicle will replace Unit 3408, a 2010 International 7400, that meets the City's established replacement criteria. Fleet lifecycle decisions are reviewed and approved by the Operations Superintendent in coordination with the Public Works Director to ensure timely and cost-effective equipment replacement.

FISCAL IMPACT:

Vendor	Fiscal Impact	Contingency	Total Fiscal Impact
McCandless Truck Center	\$157,465.54	\$ 10,000.00	\$ 167,465.54
Holman	\$ 242,655.75	\$ 10,000.00	\$ 252,655.75
			\$ 420,121.29
Approved 2025 Budget			\$ 425,000.00
Remaining Budget			\$ 4,878.71

SUBJECT: 2025 INTERNATIONAL SNOWPLOW PURCHASE

DATE: APRIL 15, 2025

PAGE 2 OF 2

Funding for this purchase is included in the approved 2025 Capital Improvement Budget under account numbers:

301433 - 640175 for up to \$212,500.00

501498 - 640000 for up to \$127,500.00

503499 - 640000 for up to \$85,000.00

PROGRAM/SUB-PROGRAM IMPACT:

A safe well-maintained, effective and efficient water distribution, sewer collections, stormwater conveyance and multi-modal transportation system including snow plowing operations at a reasonable cost.

RECOMMENDATION:

Staff recommends City Council authorize the Public Works Director to enter purchasing agreements with:

1. McCandless Truck Center, LLC in the amount of \$167,465.54 for one (1) 2026 International HV515 chassis.

2. Holman in the amount of \$252,655.75 for the installation of dump body, snowplow, wing, spreader, control systems, and related accessories.

ATTACHMENTS:

1. McCandless Truck Center Quote: 2026 International HV515 SFA Chassis.
2. Holman Quote: Henderson Snow and Ice Equipment, Tarp, Spreader, Wing, and Accessories.
3. CDOT Class 8 Truck Upfit Competitive Bid Award.

Prepared For:

CITY OF LOUISVILLE
Ben Francisco
749 Main St.
Louisville, CO 80027-1829
(303)335 - 4780
Reference ID: 2025-26 BUILD

Presented By:

MCCANDLESS TRUCK CENTER LLC
Ken Conway
16704 EAST 32ND AVENUE
AURORA CO 80011 -
(303)739-9900

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Price does not include government mandates, TARIFFS and associated costs, specification changes, destination charges, surcharges (including but not limited to fuel, steel, aluminum other raw materials), vendor price increases and availability, that may be implemented.



Model Profile
2026 HV515 SFA (HV515)

AXLE CONFIG:	6X4
MISSION:	Requested GVWR: 60000. Calc. GVWR: 60000. Calc. GCWR: 125000
DIMENSION:	Wheelbase: 217.00, CA: 131.60, Axle to Frame: 67.00
ENGINE, DIESEL:	{International S13} EPA 2024, 475HP @ 1800 RPM, 1750 lb-ft Torque @ 900 RPM, 2000 RPM Governed Speed, 475 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 4500 RDS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity
AXLE, REAR, TANDEM:	{Meritor MT-40-14X-5DCR-P} Single Reduction, 40,000-lb Capacity, with Lube Oil Pump, .5"(12.7mm) Wall Housing Thickness, Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, R Wheel Ends Gear Ratio: 4.63
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 315/80R22.5 Load Range L HAU 3 WT (CONTINENTAL), 480 rev/mile, 68 MPH, All-Position
TIRE, REAR:	(8) 11R22.5 Load Range H HDR2+ (CONTINENTAL), 491 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, AIR, TANDEM:	{Hendrickson PRIMAXX EX} 46,000-lb Capacity, 56" Axle Spacing, 9.0" Ride Height, with Shock Absorbers
PAINT:	Cab schematic 100WW Location 1: 9219, Winter White (Std) Chassis schematic N/A

Description

Base Chassis, Model HV515 SFA with 217.00 Wheelbase, 131.60 CA, and 67.00 Axle to Frame.

F/R Wt	Tot Wt
(lbs)	(lbs)
8102/4548	12650

AXLE CONFIGURATION

AXLE CONFIGURATION 6x4

0/0	0
-----	---

Notes

: Pricing may change if axle configuration is changed.

ENGINE

ENGINE, DIESEL {International S13} EPA 2024, 475HP @ 1800 RPM, 1750 lb-ft Torque @ 900 RPM, 2000 RPM Governed Speed, 475 Peak HP (Max)

0/0	0
-----	---

EMISSION, CALENDAR YEAR {International S13} EPA, OBD and GHG Certified for Calendar Year 2025

0/0	0
-----	---

CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty

0/0	0
-----	---

CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations

0/0	0
-----	---

EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Door

0/0	0
-----	---

VEHICLE REGISTRATION IDENTITY ID for Non-CARB Omnibus and/or Non-ACT Adopting State or Exempt Vehicle. Not for use on vehicles registering in CA/MA /OR/NJ/NY/WA. Contains non-mitigated legacy engine & cannot be registered in CA unless exempt. You may be held liable under state law for failure to properly register vehicle.

0/0	0
-----	---

RADIATOR Aluminum, Cross Flow, 1144 SqIn, with 1007 SqIn Charge Air Cooler

0/0	0
-----	---

FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed

0/0	0
-----	---

Includes

: FAN Nylon

AIR CLEANER Dual Element, with Integral Snow Valve and In-Cab Control, Engine Mounted

5/0	5
-----	---

ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection

0/0	0
-----	---

BLOCK HEATER, ENGINE {Phillips} 120V/1500W

4/0	4
-----	---

Includes

: BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door

ENGINE CONTROL, REMOTE MOUNTED for PTO, for N13/A26/S13 Engines

0/0	0
-----	---

FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted

0/0	0
-----	---

HOSE CLAMPS, RADIATOR HOSES , Mechanical Type; with Constant-Tension Functionality

0/0	0
-----	---

POWERTRAIN INTERFACE MODULE

0/0	0
-----	---

PTO EFFECTS, ENGINE FRONT for N13/A26/S13 Engines, Less PTO, Unit, Includes Adapter Plate on Engine Front Mounted

0/0	0
-----	---

TRANSMISSION

TRANSMISSION, AUTOMATIC {Allison 4500 RDS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway

267/103	370
---------	-----

TRANSMISSION TCM LOCATION Located Inside Cab

0/0	0
-----	---

Description

	F/R Wt (lbs)	Tot Wt (lbs)
ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS) and Regional Haul Series (RHS), General Purpose Trucks, Package Number 223, Modified for Single Input Auto Neutral	0/0	0
AUTOMATIC NEUTRAL Allison Transmission Shifts to Neutral When Parking Brake is Engaged and Remains in Neutral When Parking Brake is Disengaged, without On/Off Switch	0/0	0
NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released	0/0	0
OIL COOLER, TRANSMISSION {Modine} Water to Oil Type	25/0	25
PTO LOCATION Customer Intends to Install PTO at Left Side of Transmission	0/0	0
SHIFT CONTROL PARAMETERS {Allison} 3000 or 4000 Series Transmissions, Performance Programming	0/0	0
TRANSMISSION OIL Synthetic; 63 thru 76 Pints	0/0	0
TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission	1/0	1

CLUTCH

CLUTCH Omit Item (Clutch & Control)	-77/-20	-97
-------------------------------------	---------	-----

REAR AXLES, SUSPENSIONS

AXLE, REAR, TANDEM {Meritor MT-40-14X-5DCR-P} Single Reduction, 40,000-lb Capacity, with Lube Oil Pump, .5"(12.7mm) Wall Housing Thickness, Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, R Wheel Ends . Gear Ratio: 4.63	0/1915	1915
SUSPENSION, REAR, AIR, TANDEM {Hendrickson PRIMAAX EX} 46,000-lb Capacity, 56" Axle Spacing, 9.0" Ride Height, with Shock Absorbers	0/1053	1053
AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 50 thru 64.99 Pints	0/0	0
PDL WARNING BUZZER Power Divider Lock	0/0	0
SUSPENSION AIR CONTROL VALVE Pressure Release Control In Cab	0/1	1

FRONT AXLES

AXLE, FRONT NON-DRIVING {Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity	203/0	203
---	-------	-----

FRONT SUSPENSIONS

SUSPENSION, FRONT, SPRING Multi-Stage Parabolic Taper Leaf, Shackle Type, 20,000-lb Capacity, with Shock Absorbers	166/0	166
SPRINGS, FRONT AUXILIARY Air Bag, Right Side Only, Driver Control	15/0	15

CABS, COWLS, BODIES

CAB Conventional, Day Cab	0/0	0
ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab	0/0	0
AIR CONDITIONER with Integral Heater and Defroster	0/0	0
ARM REST, LEFT, PASSENGER SEAT	3/0	3
ARM REST, RIGHT, DRIVER SEAT	3/0	3

Description

	F/R Wt (lbs)	Tot Wt (lbs)
AUTOMATIC CLIMATE CONTROL Automatically Maintains Cabin Comfort Based on Selected Temperature	0/0	0
CAB INTERIOR TRIM Diamond, for Day Cab	0/0	0
<u>Includes</u>		
: CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger		
: DOME LIGHT, CAB Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Reading Lights; Integral to Overhead Console, Center Mounted		
: SUN VISOR (3) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Vanity Mirror and Toll Ticket Strap, plus 1 Auxiliary Visor (Front Only), Driver Side		
CAB REAR SUSPENSION Air Suspension, for High Cab Height	0/0	0
FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood	1/0	1
GAUGE CLUSTER Premium Level; English with English Electronic Speedometer	0/0	0
<u>Includes</u>		
: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for		
: GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure		
: WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)		
GAUGE, AIR APPLICATION	1/0	1
GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} Mounted in Instrument Panel	2/0	2
GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission	1/0	1
GAUGE, OIL TEMP, ENGINE	1/0	1
GRAB HANDLE, EXTERIOR Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, for Cab Entry Mounted Left Side at B-Pillar	3/0	3
GRAB HANDLE, CAB INTERIOR (2) Safety Yellow	0/0	0
HOSE CLAMPS, HEATER HOSE {Breeze} Belleville Washer Type	0/0	0
INSTRUMENT PANEL Wing Panel	0/0	0
IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster	0/0	0
KEYLESS ENTRY SYSTEM REMOTE with Panic and Auxiliary Buttons, Includes One Key Fob (Transmitter)	2/0	2
MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Turn Signals, Bright Heads, Black Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width	0/0	0
<u>Notes</u>		
: Mirror Dimensions are Rounded to the Nearest 0.5"		
MIRROR, CONVEX, LOOK DOWN Right Side, Bright, 6" x 10.5"	3/0	3
MIRROR, CONVEX, HOOD MOUNTED {Lang Mekra} (2) Right and Left Sides, Bright, Heated, 7.5" Sq.	19/0	19
MODESTY PANEL Painted	0/0	0
MONITOR, TIRE PRESSURE Omit	-9/-2	-11
SEAT BELT All Orange; 1 to 3	0/0	0

Description

	F/R Wt (lbs)	Tot Wt (lbs)
SEAT, DRIVER {National 2000 195} Air Suspension, High Back with Integral Head Rest, Cloth, Isolator, 8" Adjuster, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, 6-23 Degree Back Angle Adjust, Dual Shocks	0/0	0
SEAT, PASSENGER {National 2000 195} Air Suspension, High Back with Integral Headrest, Cloth, Isolator, 8" Adjuster, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, 6-23 Degree Back Angle Adjust, Dual Shocks	60/23	83
SUNSHADE, EXTERIOR Aerodynamic, Painted Roof Color, with Integral Clearance/Marker Lights	14/3	17
WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature	0/0	0
WINDSHIELD Heated, Single Piece	1/0	1
WINDSHIELD WIPER BLADES Winter Type	2/0	2

FRAMES

FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.866" x 3.622" x 0.437" (276.0mm x 92.0mm x 11.1mm); 456.0" (11582mm) Maximum OAL	225/459	684
BUMPER, FRONT Swept Back, Steel, Painted 0001 Canyon Black, Heavy Duty	0/0	0
CROSSMEMBER, FRONT for Hydraulic Pump, Mounting Flange to Accommodate Pump	42/3	45
FRAME EXTENSION, FRONT Integral; 20" In Front of Grille	139/-34	105
TOW HOOK, FRONT (2) Frame Mounted	8/0	8
WHEELBASE RANGE 199" (505cm) Through and Including 264" (670cm)	240/-240	0

BRAKES

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications	0/0	0
Includes		
: BRAKE LINES Color and Size Coded Nylon		
: DRAIN VALVE Twist-Type		
: GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster		
: PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel		
: PARKING BRAKE VALVE For Truck		
: QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4		
: SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4/8x6		
AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System	0/0	0
BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake	1/0	1
BRAKES, FRONT {Bendix Spicer ADB22X} Air Disc Type, Extended Service, Size 22.5", 23,000-lb Capacity	0/0	0
BRAKE CHAMBERS, FRONT AXLE 20 SqIn, for Air Disc Brakes	1/0	1
DUST SHIELDS, FRONT BRAKE Pad and Rotor, with Air Disc Brakes	7/0	7
BRAKES, REAR {Bendix Spicer ADB22X} Air Disc Type, Extended Service, Size 22.5", 26,000-lb Capacity per Axle	0/0	0
BRAKE CHAMBERS, REAR AXLE 18/24 SqIn Spring Brake, Double Diaphragm, for Air Disc Brakes	0/0	0
DUST SHIELDS, REAR BRAKE Pad and Rotor, with Air Disc Brakes	0/14	14
PARK BRAKE CHAMBERS, ADDITIONAL (2) Spring Brake Type	0/60	60
AIR COMPRESSOR {Bendix ESS 380} 16.8 CFM, Head Unload	0/0	0
AIR COMPRESSOR DISCHARGE LINE 1/2" ID to 5/8" ID Teflon Hose, with Stainless Steel Braid; to Air Dryer	0/0	0

Description

	F/R Wt (lbs)	Tot Wt (lbs)
AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 120 psi Cut-In/140 psi Cut-Out, Integrated PuraGuard Coalescing Filtration	0/0	0
AIR DRYER LOCATION Mounted Outside Right Rail, Behind Front Wheel	0/0	0
AIR TANK LOCATION (2) Vertically Stacked, Outside Right Rail, Under Cab in Front of Aftertreatment Box, Perpendicular to Rail	0/0	0
DRAIN VALVE (2) {Berg} with Pull Chains, for Air Tanks	0/0	0
TRAILER CONNECTIONS Four-Wheel, with Hand Control Valve and Tractor Protection Valve, for Straight Truck	2/0	2

Notes

: When electronic stability control is ordered with trailer connections on a 4x2 truck, please check the operator manual for trailer weight restrictions.

STEERING

STEERING GEAR (2) {TRW (Ross) THP60/RCH60} Dual Power	0/0	0
STEERING COLUMN Tilting and Telescoping	14/5	19
STEERING WHEEL 4-Spoke; 18" Dia., Black Leather Wrapped	0/0	0

DRIVELINES

DRIVELINE SYSTEM {Dana Spicer} SPL250 Main Driveline with SPL170 Interaxle Shaft, for 6x4	1/6	7
---	-----	---

EXHAUST SYSTEMS

EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Cab Mounted Right Side	31/2	33
AFTERTREATMENT COVER Aluminum	7/2	9
ENGINE COMPRESSION BRAKE {International} for S13 Engines, with Selector Switch and On/Off Switch	0/0	0
EXHAUST HEIGHT 10'	16/11	27
MUFFLER/TAIL PIPE GUARD (1) Bright Stainless Steel	19/12	31
SWITCH, FOR EXHAUST 2 Position, Lighted & Latching, On/Off Type, Mounted in IP, Inhibits Diesel Particulate Filter Regeneration as Long as Switch is in On Position	2/0	2
TAIL PIPE (1) Turnback Type, Bright	3/0	3

ELECTRICAL SYSTEMS

ELECTRICAL SYSTEM 12-Volt, Standard Equipment	0/0	0
---	-----	---

Includes

: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab
 : HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel
 : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever
 : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light
 : STARTER SWITCH Electric, Key Operated
 : STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector
 : TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature
 : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted		
: WIRING, CHASSIS Color Coded and Continuously Numbered		
ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, with Ignition "OFF" and any Door Opened	0/0	0
ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount	0/0	0
ANTENNA Shark Fin, Roof Mounted	1/0	1
AUXILIARY HARNESS 3.0' for Auxiliary Front Head Lights and Turn Signals for Front Plow Applications	2/0	2
BACK-UP ALARM {Preco 1059} Electronic; Solid State, Dual Function, 112 dBA	0/1	1
BATTERY BOX Steel, with Fiberglass Cover, 2-4 Battery Capacity, Mounted Left Side Perpendicular to Frame Rail, 26" Back of Cab	11/-2	9
BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 2850CCA Total, Top Threaded Stud	13/8	21
BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Sleeper, Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn	2/0	2
2-WAY RADIO Wiring Effects; Wiring with 20 Amp Fuse Protection, Includes Ignition Wire with 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab	1/0	1
CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	0/0	0
CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade	0/0	0
ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Separate Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake accommodation package with Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket	0/2	2
HEADLIGHTS LED, Heated, with Daytime Running Lights	0/0	0
HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn On if Windshield Wipers are Turned On	0/0	0
HORN, AIR (2) Single Tone, Chrome, Roof Mounted, with Lanyard Pull Cord	0/0	0
HORN, ELECTRIC (2) Trumpet Style	0/0	0
JUMP START STUD 12V, Remote Mounted	2/0	2
LIGHT, WORK, MTD UNDER HOOD (2) LED, Activates with Hood Open	0/0	0
POWER SOURCE, ADDITIONAL Auxiliary Power Outlet (APO) with USB-A Port and USB-C Port, Located in the Instrument Panel	0/0	0
RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input	3/0	3
SNOW SHIELD (2) Chrome; for Dual Air Horns	2/0	2
SPEAKERS (2) 6.5" Dual Cone Mounted in Both Doors, (2) 5.25" Dual Cone Mounted in Both B-Pillars	-1/0	-1
STARTING MOTOR {Mitsubishi Electric Automotive America DP60} 12-Volt	0/0	0
SWITCH, TOGGLE, FOR WORK LIGHT Lighted; on Instrument Panel and Wiring Effects for Customer Furnished Back of Cab Light	2/1	3
TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights	0/0	0
TRAILER AUXILIARY FEED CIRCUIT for Electric Trailer Brake Accommodation/Air Trailer ABS; with 30 Amp Fuse and Relay, Controlled by Ignition Switch	1/0	1
TURN SIGNALS, FRONT Includes LED Side Turn Lights Mounted on Fender	0/0	0

Description

F/R Wt **Tot Wt**
 (lbs) (lbs)

USB PORT One USB-A Port and One USB-C Port, Located in Instrument Panel	0/0	0
WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time	0/0	0

FRONT END

FRONT END Tilting, Fiberglass, with Three Piece Construction, Sloped Front	0/0	0
BUG SCREEN Mounted Behind Grille	5/0	5
GRILLE Stationary, Chrome Vertical Accent Bars, Chrome Surround	0/0	0
HOOD, HATCH (01) for Servicing	5/0	5
INSULATION, SPLASH PANELS for Sound Abatement	3/0	3
LOGOS EXTERIOR Model Badges	0/0	0
LOGOS EXTERIOR, ENGINE Badges	0/0	0

SPEEDOMETER, TOOLS, MISC

COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360	0/0	0
PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0
<u>Includes</u> : PAINT SCHEMATIC ID LETTERS "WM"		
PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
PROMOTIONAL PACKAGE Government Silver Package	0/0	0
SAFETY TRIANGLES	11/1	12
SPECIAL RATING, GVWR Limited to 68,000-lb GVWR	0/0	0

FUEL TANKS

FUEL TANK Top Draw, Non-Polished Aluminum, 26" Dia, 80 US Gal (303L), Mounted Left Side, Under Cab	15/9	24
DEF TANK 10.8 US Gal (41L) Capacity, Frame Mounted Outside Left Rail, Under Cab	0/0	0
FUEL HEATER PLUMBING Plumbing for Blender Valve Integrated in Fuel Water Separator, Thermostatically Controlled, for S13 Engine	0/0	0
FUEL/WATER SEPARATOR {Racor 6600} 12 VDC Electric Heater, Includes Pre-Heater, with Sight Bowl, Includes Water-In-Fuel Sensor	0/0	0
LOCATION FUEL/WATER SEPARATOR Mounted Under Hood, Left Side, Above Front Axle	0/0	0

WHEELS, TIRES - FRONT

WHEELS, FRONT {Accuride 29039} DISC; 22.5x9.00 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs, Non-Standard Offset, with .5" Thick Disc	72/0	72
(2) TIRE, FRONT 315/80R22.5 Load Range L HAU 3 WT (CONTINENTAL), 480 rev/mile, 68 MPH, All-Position	62/0	62

WHEELS, TIRES - REAR

Description

	F/R Wt (lbs)	Tot Wt (lbs)
WHEELS, REAR {Accuride 28828} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with .472" Thick Increased Capacity Disc and with Steel Hubs	0/96	96
(8) TIRE, REAR 11R22.5 Load Range H HDR2+ (CONTINENTAL), 491 rev/mile, 75 MPH, Drive	0/40	40

BODY INTEGRATION

BDY INTG, REMOTE POWER MODULE (2) Mounted Inside Cab Behind Driver Seat, Each Up to 12 Inputs (6 Analog & 6 Tri-State) and 17 Outputs (6 High Current, Max 20 amp per Channel, 6 Low Current, 2 PWM, (2) 5A, (1) 5VR), Max 100 amp Total, Includes Two Switch Packs with Latched Switches	0/0	0
BDY INTG, PTO ACCOMMODATION for Electric over Hydraulic PTO, Does Not Include Solenoids, with Latched Switch Mounted on Dash Includes Audible Alarm and Indicator Light in Gauge Cluster (Requires 1 Remote Power Module input & 1 output)	0/0	0

Services Section:

WARRANTY

WARRANTY Standard for HV513/HV515, HV613/HV615 Models, Effective with Vehicles Built July 1, 2017 or Later, CTS-2030A	0/0	0
SERVICES, TOWING Service Call to 36-Month/Unlimited Mileage to the Nearest Navistar Dealer for Navistar Warrantable Failure as Contract Defined; Includes Engine Failure if Supplier Declines Tow Coverage & ESC Supplied thru Navistar; \$550 (USA) Maximum Benefit per Incident	0/0	0
SRV CONTRACT, EXT ENGINE To 36-Month/300,000 Miles (480,000 km), Includes Engine, Engine Electronics, Turbocharger, Water Pump and Fuel Injectors, for International S13 Engines	0/0	0

Total Component Weight:	9788/8080 (lbs)	17868 (lbs)
	(lbs)	(lbs)

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.

Description	(US DOLLAR)	Price
Total Factory List Price Including Options: PREP & DELIVERY, FUEL, MUD FLAPS, ETC.	\$2,250.00	\$297,002.00
Total Preparation And Delivery: Freight	\$3,500.00	\$2,250.00
Total Freight:		\$3,500.00
Total Factory List Price Including Freight:		\$302,752.00
Less Customer Allowance:		(\$145,286.46)
Total Vehicle Price:		\$157,465.54
Total Sale Price:		\$157,465.54
Total Per Vehicle Sales Price:		\$157,465.54
Net Sales Price:		\$157,465.54

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.

Approved by Seller:

Accepted by Purchaser:

Official Title and Date

Firm or Business Name

Authorized Signature

Authorized Signature and Date

MCCANDLESS TRUCK CENTER LLC
 16704 EAST 32ND AVENUE
 AURORA CO 80011 -
 (303)739-9900

**This proposal is not binding upon the seller without
 Seller's Authorized Signature**

Official Title and Date

The TOPS FET calculation is an estimate for reference purposes only. The seller or retailer is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described herein are Navistar, Inc.'s standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.



Quote Prepared By:
Andrew Morton
Andre.Morton@holman.com

Quote #: 227281-R4.0
Quote Date: 03/14/2025
Expiration Date: 06/12/2025
Reference: 27795082

Customer Information:

Customer: Mccandless Idealease
Contact:
Email:

Sold To Customer:
CDOT Contract
Account # 14405

Bill To Customer:
Mccandless Idealease
Account # 5767

Vehicle Specification:

Year: 2025
Make: International
Model: HV515

Engine: International S13
Fuel Type: Diesel
Body Type: Conventional

Drivetrain: 4WD
Wheelbase: 217.0
Cab/Axle: 0.0

Notes and Special Instructions:

***** NOTES TO CUSTOMER *****

City Of Louisville: Snow and Ice: Standard / Wing
CDOT Award: 371002039

Quoted Items:

Item	Description	Item Details	Price	
1	Henderson: RSP19 - 12' Plow - GR50 Steel	<u>Supply and Install</u> Henderson: RSP19 12' length - Quick Hitch Plow Length: 12' length Moldboard Trip: Full trip with 2 external compression springs Pushframe Type: Standard Circle Frame with Top Mount Cyl Adjustable Trip: 5 Position Adj. Trip Spring Preload Moldboard Height: 48" height Moldboard Shield: Integral shield Moldboard Options Moldboard Sheet Material: 10 GA GR50 steel (standard) Hydraulic Cylinders: 3" x 1 1/2" x 10" reversing Paint: Henderson Orange Options/Accessories 12" Rubber Deflector: Yes, w/ SS Backer 36" Plastic Side Markers, Pair: Yes Parking Jack, Screw Adjustable: Yes Install Parking Jack: Yes Cutting Edge: 3/4" x 6" Carbide Cutting Edge Hitches Hitch, Plow Portion: Quick Hitch Plow portion hitch width: 30.5" Plow Portion Installed on Plow: Yes Hitch, Truck Portion: See HPH or HCH for Truck portion hitch Snow Plow Hitch: Plow Cylinders Reversing Cylinder Style: None or Top mount reversing cylinders Hitch Type Plow Portion Hitch: Plow portion picked under plow Hitch, Truck Portion: Pin hitch, low profile, 30.5" Lift Cylinder Hydraulic Lift Cylinder: 3" x 2" x 10" Double Acting Nitrided Lift Cylinder, std Lighting and Accessories - Heated LED Snow Plow Lights ** <i>Installed to factory switch in cab dash</i> ** <i>Mounted on Hood / Fender</i>	\$23,935.32	

Item	Description	Item Details	Price	
2	Henderson: 9' Wing System - Mid Mount	<u>Supply and Install</u> <u>Henderson 9' Wing System</u> Wing Configuration Type: Heavy Duty Wing System: Rear Of Cab System Rear Brace Location: Rear Brace Between Rear Axles Wing Side Location: Right Hand Side Trip Type: Non-Trip Moldboard Wing Braces: 1 Shock Brace Cutting Edge Length: 9' Cutting Edge Cutting Edge Material: 5/8 X 8 Top Punch Cutting Edge Moldboard Material: 10ga Gr50 Curved Moldboard Moldboard Height And Shape: 32" Straight Moldboard Moldboard Discharge: 6" Flare On Discharge W/Bead Moldboard Bottom Angle: 4 X 4 X .75 Bottom Angle Moldboard Top Flange: Moldboard Boxed-In Top Flange Moldboard Add Ons: Moldboard Center Lift Eye Front Mast Type: 8" Lift/11" Cyl Hyd Front Mast Front Mast Mount: Front Crosstube & Cheekplates Rear Support And Mast: Cheekplates W/Rear Cross Tube Moldboard Heel Lift: Front Mldbrd Heel Lift, 4" Cyl Paint: Mb Std Orange,All Else Black <u>Add Ons</u> Orange Sight Marker <u>Custom Options</u> Option 1: Between The Tandem Rear Support Option 2: Chassis: International HV515 Option 3: Chassis Suspension: Hendrickson HMX EX 460 ** <i>Install fitting plate for hydraulic connections</i>	\$21,689.38	

Item	Description	Item Details	Price	
3	Henderson: 15' MKE Dump Body - Stainless Steel	<u>Supply and Install</u> Henderson: 15' MKE Dump Body Body Size / Style Doghouse Type: Internal Body Length: 15' body length Side Height: 36" Sides Side to Floor Transition: 35 Degree Slope from Horizontal Tailgate: Bolster Encased Highlift Body Material/Construction Sides / Ends: 10 ga 201SS Sides/Headsheet Cabshield Material: 10 ga. with 7 ga. Endplates 201SS Cabshield Size: 22" X 78" (1/2 cab) 201SS Floor: 3/16" AR400 Rear Apron / Bolsters: 201 Stainless Steel Tailgate Bracing: 201 Stainless Steel Body Hinge Type: Greaseless Composite Bushing Hinge Body Hinge Paint: Yes, Rear Hinge Painted @ Factory Top Grate Screens: Standard 3/8" x 3/8" rod Hoist Trunnion Mount, Internal DH, Double Acting 1/2" SS Hydraulic Lines, Streetside Longsill Side Ladder Fold-up Side Ladder: Yes Ladder Material: 10 ga. 304 SS <i>** Install Driver Front</i> Tailgate Bolster Encased Highlift Coal Chut: Single 13" Centered Coal Chute Extended Coal Chute Handle Single Horizontal Bracing Formed Lift Loop, Interior Zinc Tailgate Chains Banjo Hook installed Asphalt Lip 12" Pin-On: 7 GA 201SS <i>** Requested to be weld on</i>	\$57,256.89	
4	Roll Rite - Electric - Double Bow Tarp - Mesh	<u>Supply and Install</u> Roll Rite - Double-Arm Electric Tarp System - Mesh - 7.7 oz. premium Mesh Tarp - Two 1000 denier polyester UV coated twisted strands <i>** Installed to rear surface of cabshield</i> - TarpMaster Motor 12V. 5 Year Warranty - TarpMaster Tarp Spool w/92" Housing - Bow Set. 98" Wide Top Tube w/ 98" Side Arms - Bow Set. Tension Bow 98" Wide Top Tube w/ 98" Side Arms - Pivot Set. 4 Spring w/ 60" Aluminum Pivot Tube - 12 Volt Smart Switch Basic Kit <i>** Integrated with Force America Tower or Dash Switches</i>	\$5,531.66	

Item	Description	Item Details	Price	
5	ECCO 3965 Series Warning Lights - Cabshield	<u>Supply and Install</u> ECCO 3965 Series Warning Lights (3) Single Color - Amber ** Installed into cabshield cutouts, (2) Forward Facing / (1) Side Facing ** (1) Installed into rear bolster ** Mounted Streetside (3) Single Color - Blue ** Installed into cabshield cutouts, (2) Forward Facing / (1) Side Facing ** (1) Installed into rear bolster ** Mounted Curbside 3965 Series - 7.5" Oval - Grommet Mount 12-24V DC - .5 Amp - IP67	\$1,277.82	
6	ECCO 3965 Series Warning Lights - Rear Bolster	<u>Supply and Install</u> ECCO 3965 Series Warning Lights (1) Single Color - Amber ** (1) Installed into rear bolster ** Mounted Streetside (1) Single Color - Blue ** (1) Installed into rear bolster ** Mounted Curbside 3965 Series - 7.5" Oval - Grommet Mount 12-24V DC - .5 Amp - IP67	\$384.48	
7	Henderson: 14' FSH-II Stainless Spreader w/ Stand	<u>Supply and Install</u> Henderson 14' FSH Salt/Sand Spreader -Hopper length: 14' -Hopper material: 201SS - 10 GA sides/ends, 7 GA sills/floor -Capacity: FSH-I 62" (11.6 CY) w/ formed chain shields -Conveyor: Dual 7" dia. auger -Gearcase: 3.6:1 planetary gearcase -Chute type: Standard Dump Over Chute -Spinner disk: Standard disk with Stainless Vanes -Inverted vee: Inverted vee, 201ss -Ladders: Rear mount, 304SS -Conveyor motor w/ integral speed sensor: Motor w/ integral speed sensor -Rear LED Spreader Light -Stand Type: HD (Tube) Stand -Material: Mild Construction -SS Bumper -Legs: Heavy Duty Legs w/ Wheel Guides	\$60,675.50	

Item	Description	Item Details	Price	
8	Cougar: Vibrator DC1600	<u>Supply and Install</u> Cougar Vibrator - DC1600 - 1600 lbs Vibrational Force - Cab control integrated into Force America Tower. <i>** Install steel mounting brackets for vibrator</i> <i>** Install to interior longsill, underside crossmember of body</i> <i>** Install grounding stud at rear of body: 3/8", Interior streetside longsill, in front of hinge opening.</i>	\$4,363.42	
9	Holman LED Work Light - Spinner	<u>Supply and Install</u> (1) LED Work Light - Clear - Square <i>**Mounted on spreader stand, streetside, facing outward.</i> Raw Lumen: 2376LM Effective Lumen: 1380LM Beam Pattern: Spot	\$203.53	
10	Force America Hydraulic Package - Stucchi Upgrade	<u>Supply and Install</u> Force America: Hydraulic Package - Front-mounted Pump (FEPTO) <i>* Hardware & Mounting kit provided</i> - Pump Shut-off Valve - Temp / Level Sender Unit - GEN 2 VT-35 w/ Poly Lid - In Tank Return Filter - Sight / Temp Gauge - Filler Breather - Magnetic Drain Plug - 100 Mesh Suction Strainer Force America: 6100 Gen 5 Can Bus Spreader Control Tower <i>* Centered on Cab floor</i> Valve Details: - 3000 PSI Max - Double Acting Hoist with 500 PSI Downside Relief - Double Acting Plow Lift with Integrated Power Float and 500 PSI Downside Relief - Double Acting Plow Angle - Double Acting Wing Toe With Integrated Counterbalance Valve - Double Acting Wing Heel With Integrated Counterbalance Valve - 0-14 GPM Auger Forward and Reverse - 0-7 GPM Prewet - 0-14 GPM Direct - 0-7 GPM Spinner - Dual Axis Joystick for Plow Control w/ Spreader Push Button - Single Axis Joystick for Hoist Control w/ Interlock Push Button - Auger Feedback Harness & Sensor - Direct Liquid Application Module and Harnessing - Truck Mount ISO Bus Kit - Wireless ARC Sensor kit w/ Mount	\$56,692.58	

Item	Description	Item Details	Price	
11	Municipal Rear Hitch Plate & Accessories - 3/4"	<u>Supply and Install</u> Rear Hitch & Accessories - Rear Hitch Plate w/ OEM DOT Lighting ** Paint Black - Trailer Glad Hands - 20 Ton Pintle; Std - Brake Controller - Trailer Provisions - 7 Pole - Mud Flaps and Brackets - Hydraulic Fitting Plate on Curbside for Sander Accessories	\$3,203.67	
12	Weight Slip & 2nd Stage MSO	<u>Supply</u> Provide weight slip and 2nd stage MSO Copy of slip to be placed in glove box Original slip and 2nd stage MSO mailed	\$150.00	
13	Force America: Camera System - Backup	<u>Supply and Install</u> Force America: 6100 Camera System Camera 1: Backup ** Installed into rear hitch area	\$715.06	
14	Force America: Camera System - Cabshield (Load Area)	<u>Supply and Install</u> Force America: 6100 Camera System Camera 2: Cabshield - Rear Facing ** Installed centered on cabshield, facing load area	\$715.06	
15	Force America: Camera System - Wing Operation	<u>Supply and Install</u> Force America: 6100 Camera System Camera 3: Wing Operation ** Install on rear wing mount to view operation	\$713.06	
16	LED Wing Whip Light - Blue	<u>Supply and Install</u> SafetyWhips® : 4' Blue LED Whip - CDOT selected whip light - Super Duty, Fully Lit - Threaded Base Connection - Orange Flag w/ Reflective Yellow "X" (Optional) ** Install as low as possible to reduce overall height of light when in stowed position. Mounting location recommended to be near the base of the wing heel. ** Install wiring on same circuit of Whelen Wing Tip strobe (Amber).	\$792.24	

Item	Description	Item Details	Price	
17	Laserline: Wing Guidance System (Complete)	<u>Supply and Install</u> Laserline: Wing Guidance System - GL3000PMC - 5mW Green Laser - Pneumatic blast function to remove debris - Control Panel <i>** Installed onto Force America Tower</i> <i>** Laser mounted to Cab roof, curbside using appropriate backing plate</i>	\$4,356.06	

Total: \$242,655.75

See last page for Terms and Conditions

(Plus any applicable taxes and additional options selected)

UPFIT TERMS

At Holman, we have built a strong brand and reputation for our work truck upfitting services. We seek to treat all of our customers as long-term business partners, providing best-in-class upfitting with the most efficient and effective methods in the industry. These Terms clarify the terms of our relationship with You. Holman's acceptance of any order is expressly limited to Your acceptance of these terms. Holman objects to any different or additional terms. If You are a party to a definitive written upfitting contract ("Definitive Contract") duly executed by You and authorized representatives of Holman, then Your Definitive Contract governs. In these Terms, "You" or "Your" means the legal entity which houses Your business, or Your applicable affiliate(s), in the event any Order is placed on behalf of Your affiliate(s).

Your purchase of vehicles and upfit services (including equipment and components) from Holman, and Your submission of a purchase order ("Order") for upfit services is Your acceptance of these Terms as binding. Holman may, from time to time, modify these Terms without prior notice to You. You will need to regularly review these Terms for modification. When these Terms are modified, the effective date shall be updated to the effective date of the modification.

1. **Your Order.**

1.1 Your Order is not cancellable (in whole or in part) at any time later than 5 business days after the date on which Holman receives your Order, as shown by the electronic delivery time stamp in Holman's system, or other means. If You cancel Your Order after such 5-business day period, then You are responsible to pay any freight or transportation fees related to the vehicle(s), equipment, or materials Holman has ordered or received to fulfill Your Order, in addition to any restocking fees, administrative charges and storage fees to the extent applicable. The price for Your Order is subject to adjustment by Holman at any time. Holman will provide You notice (which may occur via email, or telephone call) of any such adjustment to the Order price.

1.2 If Holman has commenced work on a vehicle, Your Order is not cancellable under any circumstance. For the avoidance of doubt, upon Holman's commencement of work for Your Order, You shall accept delivery of the applicable vehicle(s) and shall be liable to pay any fees related to Your Order in full.

1.3 **Modifications or Revisions to Your Order.** You may request reasonable modifications by submitting a revised purchase order to Holman. Holman reserves the right to accept or reject any revised purchased order in its sole discretion. Any such revised purchase order is not a binding Order unless and until Holman confirms its acceptance to You in writing. Holman reserves the right to complete the original Order (and issue an invoice for the original Order as set forth in Section 2), and may then require a new Order to account for the requested modifications. Any modification to an Order may result in additional expenses to Holman (e.g., expedited freight, duplicated administrative processes, additional material and labor expenses), therefore Holman may charge You reasonable modification fees (in addition to any fees under the Order). You understand modification fees may escalate depending on the timing of the modification request.

1.4 **Fitment.** Any quoted items with "!" to the right of the price indicates fitment information was not available at time of quote. Pricing was estimated based on previous years costs for budgetary purposes but pricing could change as fitment info is confirmed.

2. **Payment Terms.** Holman will invoice You upon completion of services for Your Order, unless otherwise agreed by Holman in writing. Invoiced amounts include sales and other taxes, and any other governmental charges, excluding taxes on Holman's income. Invoiced amounts also include shipping, freight, and other reasonable expenses. Invoices are due for payment in full within 30 days after the invoice date. Amounts not paid when due, bear interest from the due date at 0.5% per month.

3. **Shipment and Delivery.** Holman will arrange for shipment and if requested, Holman will engage Your designated carrier(s). Holman will ship to Your designated receiving point, and prices are FOB shipping point, with risk of loss borne by You.

4. **Risk of Loss.** Risk of loss to Your vehicle or equipment is borne by You, even when in Holman's possession, or in possession of Holman's designee, except where such loss is a direct result of Holman's negligence. For the avoidance of doubt, You will bear risk of loss for any damage to vehicles or equipment where such loss results from a Force Majeure Event (as defined in Section 15).

5. **Inspection and Acceptance of Goods.** You will inspect the vehicles upon delivery, and You are deemed to have accepted the vehicles unless You notify Holman to the contrary within 15 days following delivery. If You provide such notice of non-acceptance, then Holman may choose, in its sole discretion, to repair the vehicle(s). If Holman choose to repair the vehicle(s), then Holman will either dispatch technicians to Your location(s), or direct You to transport the Vehicle(s) to Holman's designated repair location. Repairs due to our negligence will be at Holman's expense. Transportation charges and all other repairs will be Your expense. Repair is Your exclusive remedy for rejected Vehicles.

6. **Rights.** If You fail to pay invoices in a timely manner, or otherwise breach these Terms, then Holman may suspend work on your Order(s), without penalty, liability or obligation, and pursue all remedies available.

7. **Customer Obligations.**

7.1 You must provide Holman with certain information (the "Vehicle Information") within 14 days of the chassis order date. Vehicle Information includes but is not limited to (i) required equipment and specification approval, and (ii) vehicle identification information (e.g., factory order number). Vehicle chassis that arrive without receipt of the Vehicle Information described herein may be subject to reasonable administrative and/or parking fees at Holman's sole discretion ("Parking Fees").

7.2 Vehicles located on Holman's premises or on the premises of Holman's designee, for a period of time greater than or equal to 14 days following the build-completion date as shown by the electronic time stamp in Holman's system, may be subject to Parking Fees. Holman may adjust the Parking Fees at any time with notice to You. Holman will invoice You any applicable Parking Fees on a monthly basis until the vehicle is no longer in possession of Holman or its designee.

7.3 Holman is not responsible to provide upkeep or maintenance (e.g., battery replacement, tire maintenance) for any vehicle where such vehicle is subject to Parking Fees.

8. **Confidential Information.** Neither party will disclose the other party's non-public confidential information which is marked on its face as confidential or in an accompanying writing, or should otherwise be deemed confidential by a reasonable person under the circumstances, provided Holman may share Your confidential information with its affiliates to the extent reasonably necessary to provide services to You. Holman may present ideas and concepts in performing its work, and Holman retains all right to use those ideas and concepts, and other know-how, in Our business.

9. **Compliance with Laws.** Each party shall comply with all applicable laws.

10. **Warranty.** Holman's Warranty to You limited to the Holman Upfit Warranty program, incorporated herein by reference, and which may be provided to You upon request. ALL OTHER WARRANTIES AND REPRESENTATIONS, EXPRESS OR IMPLIED, ARE DISCLAIMED, INCLUDING ANY WARRANTIES OF: (i) MERCHANTABILITY; (ii) FITNESS FOR A PARTICULAR PURPOSE; (iii) TITLE; OR (iv) NON-INFRINGEMENT. Any indemnification or other liability Holman might owe is strictly limited to third party claims of death, bodily injury or property damage caused solely and directly by Holman's negligence, gross negligence, or willful misconduct.

11. **LIMITATION OF LIABILITY.** NEITHER PARTY IS LIABLE TO THE OTHER FOR ANY CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS), INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY OR PUNITIVE DAMAGES.

12. **Notices.** Any notice required or permitted under these Terms shall be in a writing, signed by the notifying party and delivered by hand or recognized overnight courier, or mailed by US mail, postage prepaid, registered or certified, return receipt requested, addressed to Holman at 1420 Brewster Creek Boulevard, Bartlett, IL 60103. Notice is given when received as evidenced by the delivery receipt or if receipt is refused, the first date receipt is refused as evidenced by the delivery receipt. Notice to You shall be at Your address of record on Your most recent order.

13. **Severability.** If any of these Terms is unenforceable in any jurisdiction, such unenforceability shall not affect the rest of these Terms. On a determination that any term is unenforceable, the court may modify these Terms to give effect to the original intent of the parties.

14. **Choice of Law and Venue.** These Terms are governed by New Jersey law, without regard to its conflict of laws rules, and the UN Convention on the International Sale of Goods is excluded. Any litigation under these Terms shall be commenced and maintained in US District Court, District of New Jersey, sitting in Camden, New Jersey, or if jurisdiction is lacking, in New Jersey state court, sitting in Burlington County, New Jersey. **Each party waives the right to jury trial.**

15. **Force Majeure.** Holman shall not be liable for, nor be deemed to have defaulted under these Terms, for any failure or delay in performing any services (except for obligations to make payments), when and to the extent the failure or delay is caused by or results from acts beyond the impacted party's reasonable control (including but not limited to natural disasters, hail, floods, or other weather events, epidemics, pandemics and other public health threats, embargoes, explosions, riots, wars or acts of invasion or terrorism, requirements of law, national or regional emergency, strikes, labor stoppages or slowdowns, or shortage of adequate power or transportation) (each, a "Force Majeure Event").

16. **Waiver.** No waiver by Holman of any of these Terms is effective unless in writing and signed by an authorized representative of Holman. No failure by Holman to exercise, or delay in exercising, any right or remedy arising from these Holman Terms is or shall be a waiver thereof. No single or partial exercise of any right or remedy hereunder limits any other or further exercise thereof or the exercise of any other right or remedy.

Accepted By: _____

Date: _____



COLORADO

Department of Transportation

NOTICE OF AWARD RENEWAL COLORADO DEPARTMENT OF TRANSPORTATION

AWARD NUMBER 371002039 (THIS IS NOT A PURCHASE ORDER, SEE NOTE BELOW)	Re: Invitation For Bid # HAA IFB 24-052 RM <i>Truck Bodies and Attachments for Class 8 Trucks</i> Period Covered: 04/18/2024 through 04/17/2025 FOUR (4) possible renewal options remaining
VENDOR NO. 1106277 VENDOR NAME: Auto Truck Group ADDRESS: 1420 Brewster Creek Blvd Bartlett IL 60103 CONTACT: Jake Yezek PHONE: 720-413-9986 EMAIL: jake.yezek@holman.com	INVOICE TO: Invoice address on Purchase Order for Colorado State Agencies, Institutions and political subdivisions
DELIVERY: 180 days after receipt of chassis	COMMODITY NUMBERS: 07051

This award is for *Truck Bodies and Attachments for Class 8 Trucks* per the terms and conditions of CDOT IFB 24-052 RM and this award.

<i>Item</i>	<i>Make and Model of Product Offered</i>	<i>Unit Price of Each \$</i>
15' Dump	See additional pages	\$33,769
14' V-box Combo Unit	See additional pages	\$40,444
Liquid Anti-Icing System	See additional pages	\$23,800
12' Colorado Plow	See additional pages	\$17,004
Patrol Wing	See additional pages	\$11,137
Hydraulic Control System	See additional pages	\$67,480

Conditions of Award: Award is made to above referenced vendor for supplying the commodity/service specified above and on any attached supplementary pages per bid specifications to be ordered on an "as needed" basis beginning 04/18/2024, with (4) FOUR, one-year renewal periods, at CDOT option. This agreement is in year 1 of 5 possible years total. Prices shall be firm through the first 12 months of award. **Requests for any proposed price changes after the first 12 months must be submitted along with supporting documentation, to CDOT Purchasing, a minimum of sixty (60) days** prior to the proposed effective date of such change. A new award notice will be issued for each additional renewal year that CDOT selects. EITHER PARTY MAY CANCEL ON 30 DAYS WRITTEN NOTICE.

NOTE: THIS AWARD IS A NOTICE OF INTENT TO PURCHASE ONLY. VARIOUS CDOT PERSONNEL AS NEEDED WILL ORDER MATERIALS. MATERIAL ORDERED BY CDOT THAT COST \$5000.00 OR MORE PER ITEM, OR AGGREGATE, MUST BE ORDERED VIA PURCHASE ORDER. OTHER COLORADO STATE AGENCIES, INSTITUTIONS OR POLITICAL SUBDIVISIONS MAY ORDER MATERIALS BASED ON THIS AWARD. AGENCIES OTHER THAN CDOT ORDERING MATERIAL BASED ON THIS AWARD MUST ORDER VIA THEIR OWN PURCHASE ORDER SYSTEM.

Please direct inquiries on this award to CDOT Purchasing, Phone: 303 757 9618 Email: Jeremy.roth@state.co.us	Approved By: Jeremy Roth, Purchasing Agent
--	--